

MEGAN BARRY
MAYOR



METROPOLITAN GOVERNMENT OF NASHVILLE AND DAVIDSON COUNTY

Metropolitan Historic Zoning Commission
Sunnyside in Sevier Park
3000 Granny White Pike
Nashville, Tennessee 37204
Telephone: (615) 862-7970
Fax: (615) 862-7974

STAFF RECOMMENDATION
2106 Twentieth Avenue South
November 16, 2016

Application: Demolition—outbuilding; New construction—detached accessory dwelling unit

District: Belmont Hillsboro Neighborhood Conservation Zoning Overlay

Council District: 18

Map and Parcel Number: 10416001500

Applicant: Cheyenne Smith, Designer

Project Lead: Sean Alexander, sean.alexander@nashville.gov

Description of Project: An application to demolish an existing outbuilding and to construct a new two-story, seven-hundred square foot outbuilding, part of which may be used as a detached accessory dwelling unit (DADU).

Recommendation Summary: Staff recommends approval of the detached accessory dwelling unit with the following conditions:

1. Staff shall approve the final window and door selections prior to purchase and installation; and,
2. A restrictive covenant for the detached accessory dwelling unit shall be filed prior to issuance of a permit.


With these conditions, staff finds that the detached accessory dwelling unit meets Ordinance 17.16.030-G. and Section II.B.i of the Neighborhood Conservation zoning overlay design guidelines for this neighborhood.

The Commission does not have the authority to approve the use. This recommendation is for the design of the building based on the proposed use.


Attachments

- A:** Site Plan
B: Floorplans
C: Elevations

Vicinity Map:



Aerial Map:



Applicable Design Guidelines:

17.16.030. G. Standards for Accessory Dwelling Units:

An accessory dwelling unit should follow the design guidelines for the historic overlay and the following standards:

1. Applicability.

- a. While the following conditions listed below apply to a detached accessory dwelling they do not counter-act or over-ride the applicable life safety standards found in the code editions adopted by the Metropolitan Government of Nashville.
- b. No accessory structure shall exceed two hundred square feet when there is a detached accessory dwelling on the lot.

2. Lot Area. The lot area on which the detached accessory dwelling is to be placed shall comply with Table 17.12.020A.

3. Ownership.

- a. No more than one detached accessory dwelling shall be permitted on a single lot in conjunction with the principal structure.
- b. The detached accessory dwelling cannot be divided from the property ownership of the principal dwelling.
- c. The detached accessory dwelling shall be owned by the same person as the principal structure and one of the two dwellings shall be owner-occupied.

4. Setbacks. The setbacks for a detached accessory dwelling shall meet the setbacks found in Section 17.12.040.E. for accessory buildings.

The Commission has the ability to determine appropriate building setbacks of the required underlying base zoning for new construction, additions and accessory structures (ordinance no. BL2007-45).

Generally appropriate side setbacks for outbuildings is 3' for buildings with a 750 square foot footprint or less and 5' for buildings with a footprint greater than 750 square feet. Appropriate rear setbacks may be as close as 5'.

5. Site Requirements. A detached accessory dwelling may only be located behind the principal structure.

6. Driveway Access.

- a. On lots with no alley access, the lot shall have no more than one curb-cut from any public street for driveway access to the principal structure as well as the detached accessory dwelling.
- b. On lots with alley access, any additional access shall be from the alley and no new curb cuts shall be provided from public streets.
- c. Parking accessed from any public street shall be limited to one driveway for the lot with a maximum width of twelve feet.

7. Bulk and Massing.

- a. The living space of a detached accessory dwelling shall not exceed seven hundred square feet.
- b. On lots less than ten thousand square feet, the footprint of a detached accessory dwelling shall not exceed seven hundred fifty square feet
- c. On lots ten thousand square feet or greater, the footprint of a detached accessory dwelling shall not exceed one thousand square feet.
- d. The detached accessory dwelling shall maintain a proportional mass, size, and height to ensure it is not taller than the principal structure on the lot. The detached accessory dwelling height shall not exceed the height of the principal structure as measured to the eave line, with a maximum eave height of ten feet for single-story and seventeen feet for two-story detached accessory dwellings.
- e. The roof ridge line of the detached accessory dwelling must be less than the primary structure and shall not exceed twenty-seven feet in height.

In conjunction with the neighborhoods where DADUs are possible and using research of historic outbuildings, the Commission has determined that a 25' maximum is appropriate for historic neighborhoods. Please see design guidelines for outbuildings.

8. Design Standards.

- a. The detached accessory dwelling shall be of similar style, design and material color as used for the principal structure and shall use similar architectural characteristics, including roof form and pitch, to the existing principal structure.
- b. The detached accessory dwelling may have dormers that relate to the style and proportion of windows on the detached accessory dwelling and shall be subordinate to the roofslope by covering no more than fifty percent of the roof.
- c. Detached accessory dwellings may have dormers that are setback a minimum of two feet from the exterior wall.

9. Historic Properties.

- a. Metro Historic Zoning Commission Action. Any existing or proposed detached accessory dwelling in a historic overlay district shall comply with the adopted regulations and guidelines of the applicable historic overlay.
- b. Detached accessory dwellings with a second story dwelling unit shall enclose the stairs interior to the structure and properly fire rate them per the applicable life safety standards found in the code editions adopted by the Metropolitan Government of Nashville.

10. Restrictive Covenant. Prior to the issuance of a permit, an instrument shall be prepared and recorded with the register's office covenanting that the detached accessory dwelling is being established accessory to a principal structure and may only be used under the conditions listed above.

Note: The "use" of a DADU will require approval from the Department of Codes and Building Safety. The MHZC reviews the exterior design only, based on the intended use.

II.B. New Construction

i. Outbuildings

(Although the MHZC does not review use itself there are additional ordinance requirements for buildings that have are or have a Detached Accessory Dwelling Unit (DADU) required by ordinance 17.16.030 that are reviewed by the MHZC. This information is provided for informational purposes only and does not replace ordinance 17.16.030.)

1) A new garage or storage building should reflect the character of the period of the house to which the outbuilding will be related. The outbuilding should be compatible, by not contrasting greatly, with surrounding historic outbuildings in terms of height, scale, roof shape, materials, texture, and details.

Outbuildings: Height & Scale

- *On lots less than 10,000 square feet, the footprint of a DADU or outbuilding shall not exceed seven hundred fifty square feet or fifty percent of the first floor area of the principal structure, whichever is less.*
- *On lots 10,000 square feet or greater, the footprint of a DADU or outbuilding shall not exceed one thousand square feet.*
- *The DADU or outbuilding shall maintain a proportional mass, size, and height to ensure it is not taller or wider than the principal structure on the lot. The DADU or outbuilding height shall not exceed the height of the principal structure, with a maximum eave height of 10' for one-story DADU's or outbuildings and 17' for two-story DADUs or outbuildings. The roof ridge height of the DADU or outbuilding must be less than the principal building and shall not exceed 25' feet in height.*

Outbuildings: Character, Materials and Details

- *Historically, outbuildings were either very utilitarian in character, or (particularly with more extravagant houses) they repeated the roof forms and architectural details of the houses to which they related. Generally, either approach is appropriate for new outbuildings. DADUs or out buildings located on corner lots should have similar architectural characteristics, including roof form and pitch, to the existing principal structure.*
- *DADUs or outbuildings with a second story shall enclose the stairs interior to the structure and properly fire rate*

them per the applicable life safety standards found in the code editions adopted by the Metropolitan Government of Nashville.

Outbuildings: Roof

- Roof slopes on simple, utilitarian buildings do not have to match the roof slopes of the main structure, but generally should maintain at least a 4/12 pitch.
- The DADU or outbuilding may have dormers that relate to the style and proportion of windows on the DADU and shall be subordinate to the roof slope by covering no more than fifty percent of the roof plane and should sit back from the exterior wall by 2'.

Outbuildings: Windows and Doors

- Publicly visible windows should be appropriate to the style of the house.
- Double-hung windows are generally twice as tall as they are wide and of the single-light sash variety.
- Publicly visible pedestrian doors must either be appropriate for the style of house to which the outbuilding relates or be flat with no panels.
- Metal overhead doors are acceptable on garages when they are simple and devoid of overly decorative elements typical on high-style wooden doors. Decorative raised panels on publicly visible garage doors are generally not appropriate.
- For street-facing facades, garages with more than one-bay should have multiple single doors rather than one large door to accommodate more than one bay.

Outbuildings: Siding and Trim

- Brick, weatherboard, and board-and-batten are typical siding materials.
 - Exterior siding may match the existing contributing building's original siding; otherwise, siding should be wood or smooth cement-fiberboard lap siding with a maximum exposure of five inches (5"), wood or smooth cement-fiberboard board-and-batten or masonry.
 - Four inch (4" nominal) corner-boards are required at the face of each exposed corner.
 - Stud wall lumber and embossed wood grain are prohibited.
 - Four inch (4" nominal) cornerboards and casings around doors, windows, and vents within clapboard walls is required. Trim should be thick enough to extend beyond the clapboard. Double or triple windows should have a 4" to 6" mullion in between.
- Brick molding is required around doors, windows, and vents within masonry walls but is not appropriate on non-masonry clad buildings.

2) Outbuildings should be situated on a lot as is historically typical for surrounding historic buildings.

Generally new garages should be placed close to the alley, at the rear of the lot, or in the original location of an historic accessory structure.

Lots without rear alleys may have garages located closer to the primary structure. The appropriate location is one that matches the neighborhood or can be documented by historic maps.

Generally, attached garages are not appropriate; however, instances where they may be are:

- Where they are a typical feature of the neighborhood; or
- When the location of the attached garage is in the general location of an historic accessory building, the new garage is located in the basement level, and the vehicular access is on the rear elevation.

Setbacks & Site Requirements.

- To reflect the character of historic outbuildings, new outbuildings for duplexes should not exceed the requirements for outbuildings for the entire lot and should not be doubled. The most appropriate configurations would be two 1-bay buildings with or without parking pads for additional spaces or one 2-bay building.
- A DADU or outbuilding may only be located behind the principal structure in the established rear yard. The DADU or outbuilding is to be subordinate to the principal structure and therefore should be placed to the rear of the lot.
- There should be a minimum separation of 20' between the principal structure and the DADU or outbuilding.
- At least one side setback for a DADU or outbuilding on an interior lot, should generally be similar to the principle dwelling but no closer than 3' from each property line. The rear setback may be up to 3' from the rear property line. For corner lots, the DADU or outbuilding should match the context of homes on the street. If there is no context, the street setback should be a minimum of 10'.

Driveway Access.

- *On lots with no alley access, the lot shall have no more than one curb-cut from any public street for driveway access to the principal structure as well as the detached accessory dwelling or outbuilding.*
- *On lots with alley access, any additional access shall be from the alley and no new curb cuts shall be provided from public streets.*

Parking accessed from any public street shall be limited to one driveway for the lot with a maximum width of twelve feet.

Additional Requirements for DADUs from Ordinance 17.16.030. See requirements for outbuildings for additional requirements.

- *The lot area on which a DADU is placed shall comply with Table 17.12.020A.*
- *The DADU may not exceed the maximums outlined previously for outbuildings.*
- *No additional accessory structure shall exceed two hundred square feet when there is a DADU on the lot.*

Density.

- *A DADU is not allowed if the maximum number of dwelling units permitted for the lot has been met.*

Ownership.

- a. No more than one DADU shall be permitted on a single lot in conjunction with the principal structure.*
- b. The DADU cannot be divided from the property ownership of the principal dwelling.*
- *The DADU shall be owned by the same person as the principal structure and one of the two dwellings shall be owner-occupied.*
- *Prior to the issuance of a permit, an instrument shall be prepared and recorded with the register's office covenanting that the DADU is being established accessory to a principal structure and may only be used under the conditions listed here.*

Bulk and Massing.

- *The living space of a DADU shall not exceed seven hundred square feet.*

V. DEMOLITION

1. Demolition is not appropriate

- a. if a building, or major portion of a building, is of such architectural or historical interest and value that its removal would be detrimental to the public interest; or
- b. if a building, or major portion of a building, is of such old or unusual or uncommon design and materials that it could not be reproduced or be reproduced without great difficulty and expense.

2. Demolition is appropriate

- a. if a building, or major portion of a building, has irretrievably lost its architectural and historical integrity and significance and its removal will result in a more historically appropriate visual effect on the district;
- b. if a building, or major portion of a building, does not contribute to the historical and architectural character and significance of the district and its removal will result in a more historically appropriate visual effect on the district; or
- c. if the denial of the demolition will result in an economic hardship on the applicant as determined by the MHZC in accordance with section 17.40.420 (Historic Zoning Regulations), Metropolitan Comprehensive Zoning Ordinance.

Background: 2106 Twentieth Avenue South is a circa 1930 brick Craftsman house that contributes to the historic character of the Belmont-Hillsboro Neighborhood Conservation Zoning Overlay.



Analysis and Findings: The application is to demolish an existing outbuilding and to construct a new two-story outbuilding. The new building will have a garage on the ground floor with a dwelling unit above.

Staff recommends receipt of the restrictive covenant for the DADU prior to issuance of the preservation permit.

Demolition: The applicant proposes to demolish an existing two-car garage on the site. The garage may be the same outbuilding that appears on the 1931 and 1957 Sanborn Maps. Even if the structure does date to the 1950s or earlier, staff finds that it does not contribute to the historic character of the site or the Belmont-Hillsboro neighborhood as a whole. Staff therefore finds that the proposed demolition meets Section V.B.2 for appropriate demolition and does not meet Section V.B.1 for inappropriate demolition.

Zoning Requirements for DADU:

The answer to each of these questions must be “no.”

	YES	NO
Does the lot NOT comply with Table 17.12.020A of the zoning code? (It isn't zoned two-family or doesn't have adequate square footage to be a legally conforming lot.)		No
Are there other accessory buildings on the lot that exceed 200 square feet?		No
Is the property zoned single-family?		No
Are there already two units on the property?		No
Does the property owner NOT live on site or does NOT plan to move to this location once the DADU is complete?		No
Is the planned conditioned living space more than 700 square feet?		No
Are the stairs unenclosed		No

The project meets the zoning requirements in section 17.16.30.G. of the ordinance.

Site Planning & Setbacks:

	MINIMUM	PROPOSED
Building located towards rear of lot	n/a	Yes
Space between principal building and DADU/Garage	20'	27' (from rear of original building)
Rear setback	3'	54'
L side setback	3'	24'
R side setback	3'	3'
How is the building accessed?	From the alley or existing curb cut	Existing curb cut
If the building is two-bay and the vehicular doors face the street, are there two different doors rather than one large door?	Two-bay	Yes

The new outbuilding, which will be in the approximate location of the previous outbuilding, meets sections II.B.h.1 of the design guidelines and 17.16.30.G.4 of the Metro Code of Ordinances.

Massing Planning: The following tables show the height and scale of outbuildings permitted under the design guidelines for a lot less than 10,000 square feet in area:

Height:

	Existing conditions (height of historic building - measured from finished floor)	Potential maximums (heights to be measured from grade)	Proposed (should not exceed the lesser number to the left)
Ridge Height	26'	25'	23'-6"
Eave Height	17' (average)	2 story, 17'	2 story, 17'

The existing principle building is 1.5 stories and the proposed outbuilding is 2 stories; however, because of a drop in grade at the back of the principle building the average eave and ridge heights, taken at each corner, allows for a two-story outbuilding.

Footprint:

Area	Lot is less than 10,000 sq. ft.	Proposed footprint cannot exceed the number to the left
Maximum Square Footage	750 sq. ft.	700 sq. ft.

The project meets section II.B.h.1 of the design guidelines and 17.16.30.G. 7 of the ordinance.

Roof Shape & Elements:

Shape:

Proposed Element	Proposed Form	Typical of district?
Primary form	Front-oriented gable	X
Primary roof slope	6:12	X
Porch form	Gable over pedestrian door only	X
Porch roof slope	6:12	X

Elements:

	YES	NO
If dormers are used, do they cover less than 50% of the roof plane where they are located as measured from side-to-side?	n/a	
If dormers are used, do they sit back from the wall below by at least 2'?	n/a	
Is the roof pitch at least 4/12?	Yes	

Staff finds the roofs to be similar to the roofs of historic outbuildings, and that the project meets Section II.B.h.1 of the design guidelines and section 17.16.030.G.8 of the ordinance.

Design Standards: The building will have a two-story front-oriented gable form, which Staff finds to be compatible with the cross-gabled bungalow form of the historic house. The accessory structure has a simple, utilitarian design that is appropriate for outbuildings, with three-over-one double-hung windows that match those of the house. Typically the Commission requires two separate doors, as proposed, when a garage faces the street, which is the case here. The design and overall character of the building will be compatible with the principal structure and will meet section II.B.h.1 of the design guidelines and Section 17.16.030.G.8 of the ordinance.

Materials:

	Proposed	Color/Texture	Approved Previously or Typical of Neighborhood	Requires final Review
Foundation	Concrete slab	Natural color	X	
Cladding	Cement-fiber	Smooth, match siding on house	X	
Roofing	Asphalt shingle	Match house	X	

Trim	Cement fiber	smooth	X	
Porch Floor	Concrete slab	natural	X	
Porch Posts	Wood brackets	n/a	X	
Porch Roof	Asphalt shingle	Match house	X	
Driveway	Asphalt (existing)	black	X	
Windows	Material not indicated	Not known		X
Pedestrian Door	Material not indicated	Not known		X
Vehicular Door	Material not indicated	Not known		X

With the staff's final approval of the windows and doors and material information that has not yet been provided, staff finds that the known materials meet Section II.B.h.1 of the design guidelines.


Appurtenances & Utilities: The location of the new building's utility connections and HVAC units is not indicated on the plans. Staff recommends that the HVAC be located beyond the midpoint of the building or on the rear in order to meet section II.B.h.1 of the design guidelines.

Recommendation: Staff recommends approval of the detached accessory dwelling unit determination with the following conditions:

1. Staff shall approve the final window and door selections prior to purchase and installation; and,
2. A restrictive covenant for the detached accessory dwelling unit shall be filed prior to issuance of a permit.

With these conditions, staff finds that the detached accessory dwelling unit meets Ordinance 17.16.030-G. and Section II.B.i of the Neighborhood Conservation zoning overlay design guidelines for this neighborhood.

The Commission does not have the authority to approve the use. This recommendation is for the design of the building based on the proposed use.




On the left is a photo of the existing garage; On the right is the 1957 Sanborn map showing a garage in the approximate location of the existing garage.



2106 Twentieth Avenue South, rear. Dormer, gabled-wing, and deck were added in 2007.

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212



- ① 10'-3" EAVE HEIGHT
- ② 11'-6" EAVE HEIGHT
- ③ 22'-6" EAVE HEIGHT
- ④ 23'-9" EAVE HEIGHT
- 17'-0" AVERAGE EAVE HEIGHT
- 25'-0" AVERAGE RIDGE HEIGHT
- NOTE: FIELD VERIFY GRADE CONDITIONS, EXCAVATE AS NECESSARY TO MAINTAIN AVERAGE GRADE TO RIDGE AND EAVE HEIGHTS

01 SITE PLAN

Scale: 1:250

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		


CONSTRUCTION DRAWINGS

PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1:250

A100

SITE PLAN



CONSTRUCTION NOTES

1. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND DETAILS PRIOR TO CONSTRUCTION AND REPORT ANY DISCREPANCIES TO DESIGNER AND/OR HOMEOWNER BEFORE PROCEEDING.
2. DO NOT SCALE DRAWINGS - IF DIMENSIONS ARE IN QUESTION, THE CONTRACTOR SHALL OBTAIN CLARIFICATIONS FROM THE DESIGNER AND/OR HOMEOWNER.
3. ALL WALLS ARE 2X4 (3 1/2") UNLESS OTHERWISE NOTED. FRAMING DIMENSIONS ARE FACE OF STUD TO FACE OF STUD.
4. ALL ANGLED WALLS ARE 135° UNLESS OTHERWISE NOTED.
5. TOP OF ALL DOORS AND WINDOWS FRAMED AT 6'-8" A.F.F. UNLESS OTHERWISE NOTED.
6. INTERIOR DOORS AND CASSED OPENINGS (ROUGH OPENINGS) SHALL BE LOCATED AS GRAPHICALLY SHOWN AND EITHER BE CENTERED IN THE WALL OR LOCATED 5-1/2" FROM THE ADJACENT WALL ON THE HINGE SIDE WHILE MAINTAINING 5-1/2" ON THE LATCH SIDE UNLESS OTHERWISE NOTED.
7. CABINETRY, BUILT-INS AND SHELVING TO BE COORDINATED WITH HOMEOWNER.
8. INTERIOR TRIM DETAILS (DOORS, BASE MOLDINGS AND DOOR/WINDOW CASINGS) TO MATCH EXISTING RESIDENCE.
9. GUTTERS AND DOWNSPOUTS TO BE FIELD LOCATED AND DRAINED INTO PVIOUS AREAS. COORDINATE W/HOMEOWNER.
10. ALL WALLS AND CEILINGS TO BE INSULATED WITH CLOSED CELL SPRAY FOAM INSULATION.

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		


CONSTRUCTION DRAWINGS

PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1/4" = 1'-0"

A101

FIRST FLOOR PLAN



CONSTRUCTION NOTES

1. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND DETAILS PRIOR TO CONSTRUCTION AND REPORT ANY DISCREPANCIES TO DESIGNER AND/OR HOMEOWNER BEFORE PROCEEDING.
2. DO NOT SCALE DRAWINGS - IF DIMENSIONS ARE IN QUESTION, THE CONTRACTOR SHALL OBTAIN CLARIFICATIONS FROM THE DESIGNER AND/OR HOMEOWNER.
3. ALL WALLS ARE 2X4 (3 1/2") UNLESS OTHERWISE NOTED. FRAMING DIMENSIONS ARE FACE OF STUD TO FACE OF STUD.
4. ALL ANGLED WALLS ARE 135° UNLESS OTHERWISE NOTED.
5. TOP OF ALL DOORS AND WINDOWS FRAMED AT 6'-8" A.F.F. UNLESS OTHERWISE NOTED.
6. INTERIOR DOORS AND CASED OPENINGS (ROUGH OPENINGS) SHALL BE LOCATED AS GRAPHICALLY SHOWN AND EITHER BE CENTERED IN THE WALL OR LOCATED 5-1/2" FROM THE ADJACENT WALL ON THE HINGE SIDE WHILE MAINTAINING 5-1/2" ON THE LATCH SIDE UNLESS OTHERWISE NOTED.
7. CABINETS, BUILT-INS AND SHELVING TO BE COORDINATED WITH HOMEOWNER.
8. INTERIOR TRIM DETAILS (DOORS, BASE MOLDINGS AND DOOR/WINDOW CASINGS) TO MATCH EXISTING RESIDENCE.
9. GUTTERS AND DOWNSPOUTS TO BE FIELD LOCATED AND DRAINED INTO PERVIOUS AREAS. COORDINATE W/HOMEOWNER.
10. ALL WALLS AND CEILINGS TO BE INSULATED WITH CLOSED CELL SPRAY FOAM INSULATION.

01 SECOND LEVEL FLOOR PLAN
653 SQ. FT.

Scale: 1/4"=1'-0"

DETACHED ACCESSORY DWELLING UNIT
2106 20TH AVE. S
NASHVILLE, TN 37212

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		

CONSTRUCTION DRAWINGS


PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1/4"=1'-0"

A102

SECOND FLOOR PLAN

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212



01 FRONT ELEVATION (WEST)


Scale: 1/4"=1'-0"

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		

CONSTRUCTION DRAWINGS
 PLOT TO FULL SCALE ON 11" X 17" PAPER
 SCALE: 1/4"=1'-0"
 A103
 FRONT ELEVATION

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212



01 RIGHT ELEVATION (SOUTH)

Scale: 1/4" = 1'-0"

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		

CONSTRUCTION DRAWINGS

PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1/4" = 1'-0"

A104

RIGHT ELEVATION

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		


CONSTRUCTION
 DRAWINGS

PLOT TO FULL SCALE
 ON 11" X 17" PAPER

SCALE: 1/4" = 1'-0"

A105

REAR ELEVATION



DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		


CONSTRUCTION DRAWINGS

PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1/4" = 1'-0"


A106

LEFT ELEVATION



01 LEFT ELEVATION (NORTH)

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212



ELECTRICAL NOTES

1. ELECTRICAL DRAWINGS ARE FOR REFERENCE ONLY. ALL ELECTRICAL WORK MUST BE PERFORMED PER CODE.
2. VERIFY LOCATION OF ALL OUTLETS, SWITCHES AND LIGHTS W/HOMEOWNER PRIOR TO INSTALLATION.

ELECTRICAL SYMBOL LEGEND

- \$ SINGLE POLE SWITCH
- \$D SINGLE POLE DIMMER SWITCH
- \$3 THREE-WAY SWITCH
- \$3D THREE-WAY DIMMER SWITCH
- \$T TIMER SWITCH
- \$/\$ TWO SINGLE POLE SWITCHES
- Ⓡ LED RECESSED LIGHT (SIZE TBD) (SEALED AND INSULATED)
- Ⓢ RECESSED CAN LIGHT W/VENT FAN
- WALL LIGHT
- ⦿ SOFFIT LIGHTS (MOTION-SENSORED)
- ⊕ CEILING FAN WITH LIGHT

01 FIRST LEVEL ELECTRIC PLAN

Scale: 1/4"=1'-0"

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		

CONSTRUCTION DRAWINGS


PLOT TO FULL SCALE ON 11" X 17" PAPER

SCALE: 1/4"=1'-0"

A101

1ST LEVEL LIGHTING

DETACHED ACCESSORY DWELLING UNIT
 2106 20TH AVE. S
 NASHVILLE, TN 37212



- ELECTRICAL NOTES**
- ELECTRICAL DRAWINGS ARE FOR REFERENCE ONLY. ALL ELECTRICAL WORK MUST BE PERFORMED PER CODE.
 - VERIFY LOCATION OF ALL OUTLETS, SWITCHES AND LIGHTS W/HOMEOWNER PRIOR TO INSTALLATION.

ELECTRICAL SYMBOL LEGEND

\$	SINGLE POLE SWITCH
\$D	SINGLE POLE DIMMER SWITCH
\$3	THREE-WAY SWITCH
\$3D	THREE-WAY DIMMER SWITCH
\$T	TIMER SWITCH
\$/\$	TWO SINGLE POLE SWITCHES
(R)	LED RECESSED LIGHT (SIZE TBD) (SEALED AND INSULATED)
(FL)	RECESSED CAN LIGHT W/VENT FAN
○	WALL LIGHT
⬇	SOFFIT LIGHTS (MOTION-SENSORED)
⋄	CEILING FAN WITH LIGHT

01 SECOND LEVEL LIGHTING PLAN Scale: 1/4"=1'-0"

ISSUE DATE: 10/27/16

REV	DATE	DESCRIPTION
△		
△		
△		

CONSTRUCTION DRAWINGS
 PLOT TO FULL SCALE ON 11" X 17" PAPER
 SCALE: 1/4"=1'-0"
A108
 2ND LEVEL LIGHTING