

DAVID BRILEY  
MAYOR



**METROPOLITAN GOVERNMENT OF NASHVILLE AND DAVIDSON COUNTY**

Metropolitan Historic Zoning Commission  
Sunnyside in Sevier Park  
3000 Granny White Pike  
Nashville, Tennessee 37204  
Telephone: (615) 862-7970  
Fax: (615) 862-7974

**STAFF RECOMMENDATION**  
**1502 Franklin Avenue**  
**August 21, 2019**

**Application:** New Construction--Addition  
**District:** Eastwood Neighborhood Conservation Zoning Overlay  
**Council District:** 06  
**Base Zoning:** R6  
**Map and Parcel Number:** 08305036000  
**Applicant:** Lindsey Sullivan and Kristian Marcy  
**Project Lead:** Paul Hoffman; [paul.hoffman@nashville.gov](mailto:paul.hoffman@nashville.gov)

**Description of Project:** This application is for a rear addition. A portion of the addition goes wider than the roof of the historic home.

**Recommendation Summary:** Staff recommends approval of the proposed addition with the conditions:

1. The addition's roof on the left side is moved to be behind the existing rear-left ridge;
2. Lap siding will be smooth-faced;
3. If HVAC or other utilities are moved, they will be located on the rear façade, or beyond the midpoint of the house. Alternative mechanical and utility locations must be approved prior to an administrative sign-off on the building permit; and,
4. Staff approve the roof color, windows and doors.


With these conditions, staff finds that the application meets Sections II.B.1 and II.B.2 for the Eastwood Neighborhood Conservation Zoning Overlay.

**Attachments**  
**A:** Photographs  
**B:** Site Plan  
**C:** Elevations

**Vicinity Map:**



**Aerial Map:**



## **Applicable Design Guidelines:**

### **II.B. GUIDELINES**

#### **1. NEW CONSTRUCTION**

##### **a. Height**

The height of the foundation wall, porch roof(s), and main roof(s) of a new building shall be compatible, by not contrasting greatly, with those of surrounding historic buildings.

##### **b. Scale**

The size of a new building and its mass in relation to open spaces shall be compatible, by not contrasting greatly, with surrounding historic buildings.

*Foundation lines should be visually distinct from the predominant exterior wall material. This is typically accomplished with a change in material.*

##### **c. Setback and Rhythm of Spacing**

The setback from front and side yard property lines established by adjacent historic buildings should be maintained. Generally, a dominant rhythm along a street is established by uniform lot and building width. Infill buildings should maintain that rhythm.

*The Commission has the ability to determine appropriate building setbacks and extend height limitations of the required underlying base zoning for new construction, additions and accessory structures (ordinance no. 17.40.410).*

*Appropriate setbacks will be determined based on:*

- The existing setback of the contributing primary buildings and accessory structures found in the immediate vicinity;*
- Setbacks of like structures historically found on the site as determined by historic maps, site plans or photographs;*
- Shape of lot;*
- Alley access or lack thereof;*
- Proximity of adjoining structures; and*
- Property lines.*

*Appropriate height limitations will be based on:*

- Heights of historic buildings in the immediate vicinity*
- Existing or planned slope and grade*

*In most cases, an infill duplex should be one building, as seen historically in order to maintain the rhythm of the street. Detached infill duplexes may be appropriate in the following instances:*

- There is not enough square footage to legally subdivide the lot but there is enough frontage and width to the lot to accommodate two single-family dwellings in a manner that meets the design guidelines;*
- The second unit follows the requirements of a Detached Accessory Dwelling Unit; or*
- An existing non-historic building sits so far back on the lot that a building may be constructed in front of it in a manner that meets the rhythm of the street and the established setbacks.*

##### **d. Materials, Texture, Details, and Material Color**

The materials, texture, details, and material color of a new building's public facades shall be visually compatible, by not contrasting greatly, with surrounding historic buildings. Vinyl and aluminum siding are not appropriate.

*T-1-11- type building panels, "permastone", E.F.I.S. and other artificial siding materials are generally not appropriate. However, pre-cast stone and cement fiberboard siding are approvable cladding materials for new construction; but pre-cast stone should be of a compatible color and texture to existing historic stone clad structures in the district; and cement fiberboard siding, when used for lapped siding, should be smooth and not stamped or embossed and have a maximum of a 5" reveal. The reveal for lap siding should not exceed 5". Larger reveals may be possible but should not exceed 8" and shall have mitered corners.*

*Shingle siding should exhibit a straight-line course pattern and exhibit a maximum exposure of seven inches (7").*

*Four inch (4") nominal corner boards are required at the face of each exposed corner.*

*Stud wall lumber and embossed wood grain are prohibited.*

*Belt courses or a change in materials from one story to another are often encouraged for large two-story buildings to break up the massing.*

*When different materials are used, it is most appropriate to have the change happen at floor lines.*

*Clapboard sided chimneys are generally not appropriate. Masonry or stucco is appropriate.*

*Texture and tooling of mortar on new construction should be similar to historic examples.*

*Asphalt shingle is an appropriate roof material for most buildings. Generally, roofing should not have strong simulated shadows in the granule colors which results in a rough, pitted appearance; faux shadow lines; strongly variegated colors; colors that are too light (e.g.: tan, white, light green); wavy or deep color/texture used to simulate split shake shingles or slate; excessive flared form in the shingle tabs; uneven or sculpted bottom edges that emphasize tab width or edges, unless matching the original roof.*

*Generally front doors should be 1/2 to full-light. Faux leaded glass is inappropriate.*

#### **e. Roof Shape**

The roof(s) of a new building shall be visually compatible, by not contrasting greatly, with the roof shape, orientation, and pitch of surrounding historic buildings.

*Roof pitches should be similar to the pitches found in the district. Historic roofs are generally between 6/12 and 12/12.*

*Roof pitches for porch roofs are typically less steep, approximately in the 3-4/12 range.*

*Generally, two-story residential buildings have hipped roofs.*

*Generally, dormers should be located on the roof. Wall dormers are not typical in the historic context and accentuate height so they should be used minimally and generally only on secondary facades. When they are appropriate they should be no wider than the typical window openings and should not project beyond the main wall..*

#### **f. Orientation**

The orientation of a new building's front facade shall be visually consistent with surrounding historic buildings.

##### *Porches*

*New buildings should incorporate at least one front street-related porch that is accessible from the front street.*

*Side porches or porte cocheres may also be appropriate as a secondary entrance, but the primary entrance should address the front.*

*Front porches generally should be a minimum of 6' deep, have porch racks that are 1'-3' tall and have posts that include bases and capitals.*

##### *Parking areas and Driveways*

*Generally, curb cuts should not be added.*

*Where a new driveway is appropriate it should be two concrete strips with a central grassy median.*

*Shared driveways should be a single lane, not just two driveways next to each other. Sometimes this may be accomplished with a single lane curb cut that widens to a double lane deeper into the lot.*

### *Duplexes*

*Infill duplexes shall have one or two doors facing the street, as seen on historic duplexes. In the case of corner lots, an entrance facing the side street is possible as long as it is designed to look like a secondary entrance.*

*In the case of duplexes, vehicular access for both units should be from the alley, where an alley exists. A new shared curb cut may be added, if no alley and no driveway exists, but the driveway should be no more than 12' wide from the street to the rear of the home. Driveways should use concrete strips where they are typical of the historic context. Front yard parking or driveways which end at the front of the house are not consistent with the character of the historic neighborhoods.*

### *Multi-unit Developments*

*For multi-unit developments, interior dwellings should be subordinate to those that front the street.*

*Subordinate generally means the width and height of the buildings are less than the primary building(s) that faces the street.*

*For multi-unit developments, direct pedestrian connections should be made between the street and any interior units. The entrances to those pedestrian connections generally should be wider than the typical spacing between buildings along the street.*

### **g. Proportion and Rhythm of Openings**

The relationship of width to height of windows and doors, and the rhythm of solids (walls) to voids (door and window openings) in a new building shall be compatible, by not contrasting greatly, with surrounding historic buildings.

*Window openings on the primary street-related or front façade of new construction should be representative of the window patterns of similarly massed historic structures within the district.*

*In most cases, every 8-13 horizontal feet of flat wall surface should have an opening (window or door) of at least 4 square feet. More leniencies can be given to minimally visible side or rear walls.*

*Double-hung windows should exhibit a height to width ratio of at least 2:1.*

*Windows on upper floors should not be taller than windows on the main floor since historically first floors have higher ceilings than upper floors and so windows were typically taller on the first floor.*

*Single-light sashes are appropriate for new construction. If using multi-light sashes, muntins should be fully simulated and bonded to the glass, and exhibit an interior bar, exterior bar, as well as a spacer between glass panes.*

*Four inch (nominal) casings are required around doors, windows and vents on non-masonry buildings.*

*Trim should be thick enough to extend beyond the clapboard. Double or triple windows should have a 4" to 6" mullion in between.*

*Brick molding is required around doors, windows and vents within masonry walls but is not appropriate on non-masonry buildings.*

### **i. Utilities**

*Utility connections such as gas meters, electric meters, phone, cable, and HVAC condenser units should be located so as to minimize their visibility from the street.*

*Generally, utility connections should be placed no closer to the street than the mid point of the structure.*

*Power lines should be placed underground if they are carried from the street and not from the rear or an alley.*

## **2. ADDITIONS**

- a. Generally, an addition should be situated at the rear of a building in such a way that it will not disturb either front or side facades.

### *Placement*

*Additions should be located at the rear of an existing structure.*

*Connections to additions should, as much as possible, use existing window and door openings rather than remove significant amounts of rear wall material.*

*Generally, one-story rear additions should inset one foot, for each story, from the side wall.*

*Additions should be physically distinguished from the historic building and generally fit within the shadow line of the existing building.*

*Additions that tie-into the existing roof must be at least 6" below the existing ridge line.*

*In order to assure that an addition has achieved proper scale, the addition should:*

- No matter its use, an addition should not be larger than the existing house, not including non-historic additions, in order to achieve compatibility in scale. This will allow for the retention of small and medium size homes in the neighborhood. The diversity of housing type and size is a character defining feature of the historic districts.*
- Additions which are essentially a house-behind-a-house with a long narrow connector are not appropriate, as the form does not exist historically. Short or minimal connections that do not require the removal of the entire back wall of a historic building are preferred.*
- Additions should generally be shorter and thinner than the existing building. Exceptions may be made when unusual constraints make these parameters unreasonable, such as:*

- An extreme grade change*

- Atypical lot parcel shape or size*

*In these cases, an addition may rise above or extend wider than the existing building; however, generally the addition should not be taller and extend wider.*

*When an addition needs to be taller:*

*Whenever possible, additions should not be taller than the historic building; however, when a taller addition is the only option, additions to single story structures may rise as high as 4' above the shadow line of the existing building at a distance of 40' from the front edge of the existing building.*

*In this instance, the side walls and roof of the addition must set in as is typical for all additions.*

*The portion of the roof that can be seen should have a hipped, side gable or clipped gable roof to help decrease the visual mass of the addition.*

*When an addition needs to be wider:*

*Rear additions that are wider than an existing historic building may be appropriate when the building is narrower than 30' or shifted to one side of the lot. In these instances, a structural alcove or channel must separate the existing building from the new addition. The structural alcove should sit in a minimum of 1' and be at least twice as long as it is deep.*

*In addition, a rear addition that is wider should not wrap the rear corner.*

*Ridge raises*

*Ridge raises are most appropriate for one-story, side-gable buildings, (without clipped gables) and that require more finished height in the attic. The purpose of a ridge raise is to allow for conditioned space in the attic and to discourage large rear or side additions. The raised portion must sit in a minimum of 2' from each side wall and can be raised no more than 2' of total vertical height within the same plane as the front roof slope.*

*Sunrooms*

*Metal framed sunrooms, as a modern interpretation of early green houses, are appropriate if they are mostly glass or use appropriate cladding material for the district, are located at the rear in a minimally visible location, are minimally attached to the existing structure, and follow all other design guidelines for additions.*

*Foundation*

*Foundation walls should set in from the existing foundation at the back edge of the existing structure by one foot for each story or half story. Exception: When an addition is a small one-room deep*

*(12' deep or less) addition that spans the width of the structure, and the existing structure is masonry with the addition to be wood (or appropriate substitute siding). The change in material from masonry to wood allows for a minimum of a four inch (4") inset.*

*Foundation height should match or be lower than the existing structure.*

*Foundation lines should be visually distinct from the predominant exterior wall material. This is generally accomplished with a change in materials.*

#### *Roof*

*The height of the addition's roof and eaves must be less than or equal to the existing structure.*

*Visually evident roof slopes should match the roof slopes of the existing structure, and roof planes should set in accordingly for rear additions.*

*Skylights should not be located on the front-facing slope of the roof. Skylights should be flat (no bubble lenses) with a low profile (no more than six inches tall) and only be installed behind the midpoint of the building).*

*Dormer additions are appropriate for some historic buildings as they are a traditional way of adding ventilation and light to upper stories.*

*The addition of a dormer that would require the removal of historic features such as an existing dormer, chimneys, cupolas or decorative feature is not appropriate.*

*Rear dormers should be inset from the side walls of the building by a minimum of two feet. The top of a rear dormer may attach just below the ridge of the main roof or lower.*

*Side dormers should be compatible with the scale and design of the building. Generally, this can be accomplished with the following:*

- New dormers should be similar in design and scale to an existing dormer on the building.*
- New dormers should be similar in design and scale to an existing dormer on another historic building that is similar in style and massing.*
- The number of dormers and their location and size should be appropriate to the style and design of the building. Sometimes dormer locations relate to the openings below. The symmetry or lack of symmetry within a building design should be used as a guide when placing dormers.*
- Dormers should not be added to secondary roof planes.*
- Eave depth on a dormer should not exceed the eave depth on the main roof.*
- The roof form of the dormer should match the roof form of the building or be appropriate for the style.*
- The roof pitch of the dormer should generally match the roof pitch of the building.*
- The ridge of a side dormer should be at least 2' below the ridge of the existing building; the cheeks should be inset at least 2' from the wall below or adjacent valley; and the front wall of the gable should setback a minimum of 2' from the wall below. (These minimum insets will likely be greater than 2' when following the guidelines for appropriate scale.)*
- Dormers should generally be fully glazed and aprons below the window should be minimal.*
- The exterior material cladding of side dormers should match the primary or secondary material of the main building.*

#### *Side Additions*

*When a lot width exceeds 60' or the standard lot width on the block, it may be appropriate to add a side addition to a historic structure. The addition should set back from the face of the historic structure (at or beyond the midpoint of the building) and should be subservient in height, width and massing to the historic structure.*

*Side additions should be narrower than half of the historic building width and exhibit a height of at least 2' shorter than the historic building.*

*To deemphasize a side addition, the roofing form should generally be a hip or side-gable roof form.*

*Commercial buildings that desire a covered open-air side additions generally should not enclose the area with plastic sides. Such applications may be appropriate if: the addition is located on the ground level off a secondary facade, is not located on a street facing side of a building, has a permanent glass wall on the portion of the addition which faces the street, and the front sits back*

*a minimum of three (3') from the front or side wall, depending on placement of the addition.*

b. The creation of an addition through enclosure of a front porch is not appropriate.

*Side porch additions may be appropriate for corner building lots or lots more than 60' wide.*

c. Contemporary designs for additions to existing properties are not discouraged when such additions do not destroy significant historical, architectural, or cultural material; and when such design is compatible, by not contrasting greatly, with the size, scale, color, material, and character of the property, neighborhood, or environment.

d. A new addition should be constructed in such a manner that if the addition were to be removed in the future, the essential form and integrity of the original structure would be unimpaired.

*Connections should, as much as possible, use existing window and door openings rather than remove significant amounts of rear wall material.*

e. Additions should follow the guidelines for new construction.

### **III.B.1 Demolition is Not Appropriate**

- a. if a building, or major portion of a building, is of such architectural or historical interest and value that its removal would be detrimental to the public interest; or
- b. if a building, or major portion of a building, is of such old or unusual or uncommon design and materials that it could not be reproduced or be reproduced without great difficulty and expense.

### **III.B.2 Demolition is Appropriate**

- a. if a building, or major portion of a building, has irretrievably lost its architectural and historical integrity and significance and its removal will result in a more historically appropriate visual effect on the district;
- b. if a building, or major portion of a building, does not contribute to the historical and architectural character and significance of the district and its removal will result in a more historically appropriate visual effect on the district; or
- c. if the denial of the demolition will result in an economic hardship on the applicant as determined by the MHZC in accordance with section 17.40.420 of the historic zoning ordinance.

**Background:** 1502 Franklin Avenue was built circa 1930 and is a contributing building in the Eastwood Neighborhood Conservation Zoning Overlay.

**Analysis and Findings:** The applicant proposes construction of a rear addition. A portion of the addition is proposed wider than the existing roof.



Figure 1: 1502 Franklin Avenue.

**Demolition:** An enclosed rear porch of three hundred and eight square feet (308 sq. ft.) will be removed to accommodate the new construction. The existing rear addition was an original porch enclosed after 1957 (Figure 2). It does not contribute to the architectural or historical character of the building due to the changes and its minimally-visible location. An existing shed in the rear yard is also proposed to be removed. This structure, built after 1957, is not contributing, and its demolition is in accordance with the design guidelines.

Staff finds that the proposed partial demolition meets Sections II.B.1 and II.B.2 for appropriate demolition.

**Location & Removability:** The addition will attach to the rear façade of the house with the walls stepped in two feet (2') on the left and twelve feet (12') on the right. The addition will have a short connector forward of its main ridge. The addition is offset to the left with a hipped roof extending over the existing roof on that side approximately twelve feet (12') (Figures 3 and 4). In general, an addition should be behind the existing roof, and should fit within the shadow line of the existing roof form. Side dormers have been permitted concurrently with a rear addition, however as proposed, this addition is not a dormer but a second level addition which cuts into the original roof form, requiring removal of a ridge of the hipped roof form. Staff recommends that this portion of the addition be moved behind the existing ridge, to minimize visibility and avoid disturbing the original roof form. The location and attachment of the remainder of the addition, impacting only the rear of the building, leaves the historic form of the house intact and would be removable without compromising the integrity of the historic structure.




Figure 2: Footprint in 1957 shows the rear porch was not yet enclosed.

With the condition that the left side of the addition is moved behind the existing rear left ridge of the hipped roof, staff finds that the location and removability meet Section II.B.2.a and d.

**Design:** The design of the addition is compatible with the historic house in its detailing, and exterior materials. The rear of the second story includes a sixty square foot (60 sq. ft.) balcony over the rear of the porch area, in a minimally-visible location. Staff finds the balcony to be appropriate in because of its minimally visible location, small size, and the fact that it not covered. As described in “Location & Removability,” the left side of the addition should be moved behind the existing roof line. The form of the addition will be distinguished from the original building by stepping in from both side walls.



Figure 3: Staff recommends this portion of the addition be moved behind the historic roof. The existing roof form is on the right and the arrow denotes the portion of the addition that cuts into the original roof form.

With the revision to the left side, staff finds that the character of the addition does not contrast with the historic building, therefore it will meet Section II.B.2.c.




Figure 4: The wide line added to the roof plan shows the ridge that will be lost with the proposed addition.

**Height & Scale:** The addition and porch will add approximately one thousand and thirty-nine square feet (1,039 sq. ft.) to the existing one thousand, five hundred and twenty-four square feet (1,524 sq. ft.) of the house. The addition has the same ridge height as the house with a connector two feet (2’) shorter than the existing ridge. On the left side, the addition encroaches into the existing roof area (see “Location & Removability”) altering the original roof form (figure 4). With the exception of this portion of the addition, the height and scale of the addition are compatible with surrounding historic buildings.

With the condition that the left side of the addition is moved behind the existing roof, Staff finds that the height and scale of the proposed addition meet Sections II.B.1a, II.B.1.b and II.B.2.

**Setback & Rhythm of Spacing:** The walls of the addition will be ten feet (10’) from the left side property line and eighteen feet (18’) from the right side. The rear of the addition is one hundred and five feet (105’) from the rear property line. The setbacks meet the regulations of five feet (5’) for the sides and twenty feet (20’) for the rear.

Staff finds the project meets section II.B.1.c for setbacks.

Materials:

	<b>Proposed</b>	<b>Color/Texture/Make/Manufacturer</b>	<b>Approved Previously or Typical of Neighborhood</b>	<b>Requires Additional Review</b>
<b>Foundation</b>	Concrete Block	n/a	Yes	No
<b>Cladding</b>	Cement fiberboard lap siding, match existing reveal	Should be smooth-faced	Yes	No
<b>Trim</b>	Cement fiber	n/a		
<b>Secondary cladding</b>	Shake shingles	Unknown	Yes	No
<b>Roofing</b>	Architectural Shingles and Standing Seam	Color requires approval	Yes	Yes
<b>Secondary roofing</b>	Metal	Color requires approval	Yes	Yes
<b>Windows</b>	Aluminum-clad	Need final approval	Yes	Yes
<b>Porch doors</b>	Wood/metal	Unknown	Unknown	Yes
<b>Porch columns</b>	Brick base, wood columns	n/a	Yes	No
<b>Porch steps and decking</b>	Composite	Unknown	Unknown	No
<b>Porch railing</b>	Metal	Unknown	Unknown	No

Lap siding should be installed with the smooth face only.

With the condition that lap siding is smooth, and staff approval of windows, doors, and roofing colors, the project meets section II.B.1.d for materials.

Roof form: The addition has a hipped roof with 8/12 pitch. The forward portion of the roof intrudes over the existing roof (see section on “Location & Removability.”) The addition includes a wall dormer on each side. Wall dormers are not appropriate in every instance; however, because of their small scale and the fact that wall is inset from the wall of the home, staff finds the dormers to be appropriate.

With the condition that the addition’s roof is moved behind the existing roof, staff finds that the project will meet Section II.B.1.e and II.B.2.

Proportion and Rhythm of Openings: No changes to the window and door openings on the existing house were indicated on the plans. The windows on the proposed addition are generally twice as tall as they are wide, meeting the historic proportions of openings. The left side dormer has four square windows. As the location is on the new construction, behind the house, and in a minimally-visible location, staff finds the square windows appropriate. There are no large expanses of wall space without a window or door opening.

Staff finds the project's proportion and rhythm of openings to meet Section II.B.1.g.

Appurtenances & Utilities: The submitted drawings do not indicate any changes to the site's appurtenances. If HVAC and other utilities are moved, staff recommends that they be located on the rear façade, or behind the midpoint of the house, for minimal visibility.

Staff finds that the project meets section II.B.1. i.

**Recommendation:**


Staff recommends approval of the proposed addition with the conditions:

1. The addition's roof on the left side is moved to be behind the existing rear-left ridge;
2. Lap siding will be smooth-faced;
3. If HVAC or other utilities are moved, they will be located on the rear façade, or beyond the midpoint of the house. Alternative mechanical and utility locations must be approved prior to an administrative sign-off on the building permit; and,
4. Staff approve the roof color, windows and doors.

With these conditions, staff finds that the application meets Sections II.B.1 and II.B.2 for the Eastwood Neighborhood Conservation Zoning Overlay.

**NOTES:**

- SITEPLAN INFORMATION BASED ON CITY GIS INFORMATION AND PRESUMED TO BE ACCURATE
- ACTUAL LOCATION OF ALL UTILITIES TO BE FIELD VERIFIED



**1** Siteplan  
1:20


**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **A.2.3**

**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

06 .26 .19

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**1** Roof Plan  
 1/8" = 1'-0"


**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **A.1.3**

**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

**06 .26 .19**

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**1** Main Level Demo Plan  
1/8" = 1'-0"


**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **D.1.1**

**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

**06.19.19**

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**1** Main Level Plan  
1/8" = 1'-0"


**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **A.1.1**

**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

**06.19.19**

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**1** Upper Level Plan  
1/8" = 1'-0"

**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **A.1.2**


**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

**06.19.19**

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



2 West Elevation  
1/8" = 1'-0"



1 East Elevation  
1/8" = 1'-0"


ADDITION TO THE SULLIVAN MARCY RESIDENCE

Sheet # A.2.1

1502 FRANKLIN AVE., NASHVILLE, TENNESSEE


06.26.19

DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**4 South Elevation**  
1/8" = 1'-0"

**3 Building Section @ Addition**  
1/8" = 1'-0"



**2 Building Section @ Existing**  
1/8" = 1'-0"

**1 North Elevation**  
1/8" = 1'-0"


**ADDITION TO THE SULLIVAN MARCY RESIDENCE**

Sheet # **A.2.2**


**1502 FRANKLIN AVE., NASHVILLE, TENNESSEE**

**06.19.19**


DRAWN BY: CHRIS CUNNINGHAM 1933 LEARNARD AVE. LAWRENCE, KS C: 785.331.5812



**2** Building Section @ Bedroom  
1/8" = 1'-0"



**1** Building Section at Bathroom  
1/8" = 1'-0"



**3** Window Types  
1/8" = 1'-0"