

**VOLUME 2  
PROCEDURES**

**STORMWATER MANAGEMENT MANUAL**



METROPOLITAN GOVERNMENT OF  
NASHVILLE AND DAVIDSON COUNTY  
DEPARTMENT OF WATER AND SEWERAGE SERVICES  
STORMWATER DIVISION  
NASHVILLE, TENNESSEE

APRIL 2012

**VOLUME 2  
PROCEDURES**

**STORMWATER MANAGEMENT MANUAL**



Prepared for

**METROPOLITAN GOVERNMENT OF  
NASHVILLE AND DAVIDSON COUNTY**

**DEPARTMENT OF WATER AND SEWERAGE SERVICES  
STORMWATER DIVISION  
NASHVILLE, TENNESSEE**



# Contents

Chapter 1	Introduction.....	1-1
	1.1 Purpose.....	1-1
	1.2 Format and Contents.....	1-1
	1.3 Limitations.....	1-3
	1.4 Updating.....	1-4
Chapter 2	Hydrology.....	2-1
	2.1 Procedure Selection.....	2-1
	2.2 Rainfall Data.....	2-4
	2.2.1 Intensity-Duration-Frequency Relationships.....	2-4
	2.2.2 Rainfall Hyetographs.....	2-5
	2.2.3 Example Problem.....	2-5
	2.3 Rainfall Excess.....	2-6
	2.3.1 Rational Method Runoff Coefficient.....	2-7
	2.3.2 SCS Curve Numbers.....	2-8
	2.3.3 Example Problems.....	2-10
	2.4 Time of Concentration.....	2-13
	2.4.1 Overland Flow.....	2-13
	2.4.2 Shallow Channel Flow.....	2-15
	2.4.3 Main Channel Flow.....	2-15
	2.4.4 Example Problem.....	2-15
	2.5 Peak Runoff Rates.....	2-18
	2.5.1 Gaged Sites.....	2-18
	2.5.2 Rational Method.....	2-19
	2.5.3 USGS Regression Equations.....	2-19
	2.5.4 SCS TR-55 Graphic Method.....	2-21
	2.5.5 Other Techniques.....	2-22
	2.5.6 Example Problems.....	2-23



2.6	Flood Hydrographs .....	2-25
2.6.1	Unit Hydrographs .....	2-25
2.6.2	Inman's Dimensionless Hydrograph .....	2-28
2.6.3	Rational Hydrograph Method .....	2-29
2.6.4	SCS TR-55 Tabular Method .....	2-30
2.6.5	Other Methods .....	2-30
2.6.6	Example Problems .....	2-31
2.7	Hydrologic Channel Routing .....	2-36
2.7.1	Muskingum Method .....	2-37
2.7.2	SCS TR-55 Tabular Method .....	2-39
Chapter 3	Open Channel Hydraulics .....	3-1
3.1	Linings .....	3-1
3.1.1	Vegetation .....	3-1
3.1.2	Flexible .....	3-2
3.1.3	Rigid .....	3-2
3.2	Design Criteria .....	3-3
3.2.1	General .....	3-3
3.2.2	Channel Transitions .....	3-3
3.2.3	Return Period .....	3-4
3.2.4	Velocity Limitations .....	3-4
3.2.5	Manning's n Values .....	3-4
3.2.6	Channel Stability Considerations .....	3-6
3.3	Uniform Flow Calculations .....	3-8
3.3.1	Geometric Relationships .....	3-9
3.3.2	Direct Solutions .....	3-9
3.3.3	Trial and Error Solutions .....	3-10
3.3.4	Critical Flow Calculations .....	3-12
3.3.5	Vegetative Design .....	3-13
3.3.6	Riprap Design .....	3-16
3.3.7	Approximate Flood Limits .....	3-18



	3.3.8	Example Problems .....	3-21
	3.4	Gradually Varied Flow .....	3-25
	3.4.1	Direct Step Method .....	3-25
	3.4.2	Standard Step Method.....	3-27
	3.4.3	Example Problems .....	3-29
	3.5	Rapidly Varied Flow.....	3-32
	3.6	Hydraulic Jump .....	3-32
	3.7	Construction and Maintenance Considerations .....	3-33
Chapter 4		Gutter and Inlet Hydraulics.....	4-1
	4.1	Design Criteria.....	4-1
	4.1.1	Return Period .....	4-1
	4.1.2	Spread .....	4-1
	4.1.3	Inlet Types and Spacing.....	4-2
	4.1.4	Manning's n Values .....	4-2
	4.1.5	Grade .....	4-2
	4.1.6	Cross Slope .....	4-2
	4.1.7	Curb and Gutter Sections.....	4-3
	4.1.8	Roadside and Median Ditches .....	4-3
	4.1.9	Bridge Decks.....	4-3
	4.2	Gutter Flow Calculations.....	4-4
	4.2.1	Nashville Standard Pavement Sections.....	4-5
	4.2.2	Uniform Cross Slopes.....	4-5
	4.2.3	Composite Gutter Sections .....	4-6
	4.2.4	Example Problems .....	4-8
	4.3	Combination Inlets.....	4-9
	4.3.1	Continuous Grade .....	4-9
	4.3.2	Sump Conditions .....	4-9
	4.4	Grate Inlets.....	4-9
	4.4.1	Continuous Grade (Nashville Standards) .....	4-10



	4.4.2	Continuous Grade (General).....	4-10
	4.4.3	Sump Conditions (Nashville Standards).....	4-11
	4.4.4	Sump Conditions (General).....	4-11
	4.4.5	Example Problems.....	4-13
Chapter 5		Culvert Hydraulics.....	5-1
	5.1	Culvert Selection.....	5-1
	5.1.1	Application.....	5-1
	5.1.2	Shape and Material.....	5-2
	5.1.3	Size.....	5-2
	5.1.4	End Treatment.....	5-2
	5.1.5	Control Section.....	5-2
	5.2	Design Criteria.....	5-3
	5.2.1	Return Period.....	5-3
	5.2.2	Headwater.....	5-3
	5.2.3	Tailwater.....	5-4
	5.2.4	Length and Slope.....	5-4
	5.2.5	Velocity Limitations.....	5-4
	5.3	Design Calculations.....	5-5
	5.3.1	General Procedure.....	5-5
	5.3.2	Inlet Control.....	5-10
	5.3.3	Outlet Control.....	5-12
	5.3.4	Tapered Inlets.....	5-14
	5.3.5	Roadway Overtopping.....	5-19
	5.3.6	Example Problems.....	5-20
Chapter 6		Storm Sewer Hydraulics.....	6-1
	6.1	Design Criteria.....	6-1
	6.1.1	Return Periods.....	6-1
	6.1.2	Manning's n Values.....	6-1
	6.1.3	Slopes and Hydraulic Gradient.....	6-2
	6.1.4	Pipe Size and Length.....	6-2
	6.1.5	Minimum Clearances.....	6-3



	6.1.6	Inlet Location and Spacing .....	6-3
	6.1.7	Easements .....	6-3
	6.2	General Approach .....	6-3
	6.3	Hydrologic Calculations .....	6-4
	6.3.1	Rational Method .....	6-4
	6.3.2	Inlet Hydrograph Method .....	6-5
	6.3.3	Example Comparison.....	6-6
	6.4	Hydraulic Calculations .....	6-6
	6.4.1	Pressure Versus Gravity Flow .....	6-6
	6.4.2	Energy Losses .....	6-7
	6.4.3	Gravity Flow .....	6-9
	6.4.4	Pressure Flow.....	6-12
	6.5	Construction and Maintenance Considerations .....	6-14
Chapter 7		Bridge Hydraulics .....	7-1
	7.1	Design Criteria.....	7-1
	7.1.1	Return Period .....	7-1
	7.1.2	High Water.....	7-1
	7.1.3	Clearances.....	7-1
	7.1.4	Average Velocity.....	7-3
	7.1.5	Relief Openings .....	7-3
	7.1.6	Spur Dikes.....	7-3
	7.1.7	Structural Design .....	7-4
	7.1.8	Structural Alterations.....	7-4
	7.2	Water Surface Profile Calculations.....	7-4
	7.3	Construction and Maintenance Considerations .....	7-5
Chapter 8		Detention/Retention Hydraulics.....	8-1
	8.1	Design Criteria.....	8-1
	8.1.1	Release Rate.....	8-2
	8.1.2	Detention Volume.....	8-2



8.1.3	Grading and Depth.....	8-3
8.1.4	Outlet Works.....	8-4
8.1.5	State Dam Safety Program.....	8-4
8.2	General Water Quality Procedures .....	8-5
8.3	General Water Quantity Procedures .....	8-5
8.4	Outlet Hydraulics.....	8-7
8.4.1	Sharp-Crested Weirs—No End Contractions .....	8-7
8.4.2	Sharp-Crested Weirs—Two End Contractions.....	8-7
8.4.3	Sharp-Crested Weirs—Submerged Discharge.....	8-8
8.4.4	Broad-Crested Weirs.....	8-8
8.4.5	V-Notch Weirs.....	8-9
8.4.6	Proportional Weirs.....	8-9
8.4.7	Orifices.....	8-10
8.5	Preliminary Detention Calculations.....	8-10
8.5.1	Storage Volumes.....	8-10
8.5.2	Peak Flow Reduction.....	8-11
8.6	Routing Calculations.....	8-12
8.6.1	Storage Indication Method.....	8-12
8.6.2	Example Problems .....	8-14
8.6.3	SCS TR-55 Graphical Method.....	8-17
8.7	Land-Locked Retention .....	8-17
8.8	Permanent Pool Facilities .....	8-18
8.8.1	Water Budget Calculations .....	8-18
8.8.2	Example Problem.....	8-19
8.9	Construction and Maintenance Considerations .....	8-20
8.10	Protective Treatment.....	8-21
Chapter 9	Erosion and Sediment Control.....	9-1
9.1	Basic Principles.....	9-1
9.2	Applying Best Management Practices.....	9-2





9.3	Universal Soil Loss Equation (USLE).....	9-2
9.3.1	Rainfall Factor (R).....	9-3
9.3.2	Soil Erodibility Factor (K).....	9-4
9.3.3	Length-Slope Factor (LS).....	9-4
9.3.4	Control Practice Factor (CP).....	9-5
9.3.5	Plan Evaluation.....	9-6
9.3.6	Example Problem.....	9-6
9.4	Erosion Control.....	9-8
9.4.1	Temporary and Permanent Considerations.....	9-8
9.4.2	Surface Stabilization Factors.....	9-9
9.4.3	Exposure Scheduling Factors.....	9-9
9.4.4	Runoff Control Factors.....	9-10
9.4.5	Slope and Channel Protection.....	9-10
9.4.6	Outlet Protection.....	9-10
9.5	Sediment Control.....	9-11
9.5.1	Temporary and Permanent Considerations.....	9-11
9.5.2	Sediment Barriers.....	9-11
9.5.3	Sediment Traps and Basins.....	9-12
9.5.4	Construction Road and Entrance Management.....	9-12
Chapter 10	Outlet Protection.....	10-1
10.1	General Procedure.....	10-1
10.2	Local Scourhole Estimation.....	10-3
10.3	Riprap Aprons.....	10-5
10.3.1	Design Procedure.....	10-5
10.3.2	Design Considerations.....	10-6
10.3.3	Example Problems.....	10-6
10.4	Riprap Outlet Basins.....	10-8
10.4.1	Design Procedure.....	10-8
10.4.2	Design Considerations.....	10-9
10.4.3	Example Problems.....	10-10



	10.5 Baffled Outlets.....	10-14
	10.5.1 Design Procedure.....	10-14
	10.5.2 Example Problem.....	10-16
	10.6 U.S. Bureau of Reclamation Type II Outlet Basin .....	10-18
	10.6.1 Supercritical Flow Expansion.....	10-18
	10.6.2 Design Procedure.....	10-21
	10.6.3 Design Considerations.....	10-22
	10.6.4 Example Problem.....	10-22
Chapter 11	Data Collection .....	11-1
	11.1 General Information.....	11-1
	11.2 Previous Studies.....	11-2
	11.2.1 MWS .....	11-2
	11.2.2 Metro Planning .....	11-2
	11.2.3 U.S. Geological Survey .....	11-2
	11.2.4 U.S. Army Corps of Engineers .....	11-3
	11.2.5 U.S. Department of Agriculture, Natural Resources Conservation Service (NRCS-Formerly SCS).....	11-4
	11.2.6 Other Studies.....	11-4
	11.3 Metropolitan Planning Commission .....	11-4
	11.4 Natural Resources Data .....	11-5
	11.4.1 Precipitation.....	11-5
	11.4.2 Soils .....	11-5
	11.4.3 Topography.....	11-6
	11.4.4 Streamflow.....	11-6
	11.4.5 Groundwater .....	11-6
	11.5 Manmade Features.....	11-7
	11.5.1 Land Use.....	11-7
	11.5.2 Impoundments .....	11-7
	11.5.3 Stream Channels .....	11-7
	11.6 Field Investigations.....	11-7



	11.6.1 Site Visits.....	11-8
	11.6.2 Stream Channels .....	11-8
	11.6.3 Survey Requirements.....	11-9
Chapter 12	Computer Programs .....	12-1
	12.1 General Guidance .....	12-1
	12.2 Flood Hydrology.....	12-1
	12.3 Open Channel Hydraulics.....	12-2
	12.4 Culverts.....	12-2
	12.5 Storm Sewers .....	12-2
	12.6 Detention Flood Routing .....	12-2
	12.7 Bridge Hydraulics.....	12-3
	12.8 Water Quality.....	12-3
Chapter 13	Stormwater Pollution Prevention Plan.....	13-1
	13.1 Introduction to SPPP.....	13-1
	13.2 SPPP Phases.....	13-2
	13.3 Construction Site SPPP.....	13-4
	13.3.1 Site Evaluation and Design.....	13-4
	13.3.1.1 Collection Site Information.....	13-4
	13.3.1.2 Develop Site Plan and Map.....	13-5
	13.3.2 Assessment.....	13-6
	13.3.3 Practice Selection / Plan Design .....	13-6
	13.3.3.1 Select Permanent Treatment Practices.....	13-7
	13.3.3.2 Select Erosion Prevention and Sediment Control (EP & SC) Practices.....	13-7
	13.3.3.3 Select Other Temporary Practices .....	13-8
	13.3.3.4 Prepare Inspection and Maintenance Plan / Requirements .....	13-8
	13.3.3.5 Prepare Phased Schedule .....	13-9
	13.3.4 Checklist, Certification / Notification.....	13-10
	13.3.4.1 General Stormwater Permit NOI Certification .....	13-10



13.3.4.2	Other Permitting Requirements Notification .....	13-10
13.3.4.3	Grading Permit Application and Review Process.....	13-10
13.3.4.4	Pre-construction Inspection	
13.3.5	Construction / Implementation .....	13-11
13.3.5.1	Implementation / Construction Practices .....	13-11
13.3.5.2	Inspection and Maintenance Practices .....	13-11
13.3.5.3	Update / Change SPPP .....	13-12
13.3.5.4	Reporting Requirements for Spilled Materials .....	13-13
13.3.6	Final Stabilization / Termination .....	13-13
13.3.6.1	Final Stabilization .....	13-13
13.3.6.2	Notice of Termination.....	13-14
13.3.6.3	Evaluate SPPP Performance .....	13-14
13.4	References.....	13-14



## List of Tables

Table 2-1	Guidelines for Selecting Hydrologic Procedures.....	2-40
Table 2-2	Balanced Storm Rainfall Hyetograph Data for Metro Nashville.....	2-42
Table 2-3	Runoff Coefficients for a Design Storm Return period of 10 Years or Less.....	2-45
Table 2-4	Design Storm Frequency Factors for Pervious Area Runoff Coefficients .	2-47
Table 2-5	Runoff Curve Numbers for Urban Areas.....	2-48
Table 2-6	Runoff Curve Numbers for Rural Areas.....	2-50
Table 2-7	Overland Flow Manning's n Values.....	2-52
Table 2-8	Current (1988) Streamflow Monitoring Sites, Metro Nashville and Davidson County .....	2-53
Table 2-9	USGS Regression Equation Parameters .....	2-55
Table 2-10	I <sub>a</sub> Values for Runoff Curve Numbers .....	2-56
Table 2-11	SCS Dimensionless Unit Hydrograph Ratios .....	2-57
Table 2-12	Time and Discharge Ratios of Inman's Dimensionless Hydrograph.....	2-58
Table 2-13	Hydrograph Computation, Example 2-9.....	2-60
Table 3-1	Maximum Velocities for Comparing Lining Materials .....	3-34
Table 3-2	Maximum Velocities for Vegetative Channel Linings .....	3-34
Table 3-3	Recommended Manning's n Values for Artificial Channels.....	3-35
Table 3-4	Classification of Vegetal Covers as to Degree of Retardance .....	3-36
Table 3-5	Coefficients for Computing Manning's n Values for Natural or Excavated Channels Using Cowans Equation .....	3-37



Table 3-6	Critical Depth Equations for Uniform Flow in Selected Channel Cross Sections.....	3-38
Table 3-7	Water Surface Profile Computation Form for the Direct Step Method .....	3-39
Table 3-8	Water Surface Profile Computation Form for the Standard Step Method .....	3-40
Table 3-9	Direct Step Method Results for Example 3-5 .....	3-41
Table 3-10	Standard Step Method Results for Example 3-6.....	3-42
Table 4-1	Manning’s n Values for Street and Pavement Gutters.....	4-14
Table 5-1	Culvert Entrance Loss Coefficients .....	5-27
Table 6-1	Data for Demonstrating the Application of Storm Sewer Hydrologic Methods .....	6-15
Table 6-2	Results of Rational Method Calculations for the Hypothetical Storm Sewer System in Figure 6-1 .....	6-15
Table 6-3	Results of Inlet Hydrograph Calculations for the Hypothetical Storm Sewer System in Figure 6-1 .....	6-16
Table 6-4	Comparison of Hydrologic Methods for the Hypothetical Storm Sewer System in Figure 6-1 .....	6-18
Table 6-5	Values of $K_2$ for Determining Loss of Head Due to Sudden Expansion in Pipes, from the Formula $H_2 = K_2 (v^2_1/2g)$ .....	6-18
Table 6-6	Values of $K_3$ for Determining Loss of Head Due to Sudden Contraction in Pipes, from the Formula $H_3 = K_3 (v^2_2/2g)$ .....	6-19
Table 6-7	Head Loss Coefficients for Manholes/Junctions .....	6-20
Table 7-1	Example Tabulation Sheet for Evaluating Bridge Plugging Potential.....	7-6
Table 8-1	Size Categories for Dams in Tennessee.....	8-22



Table 8-2	Minimum Freeboard Design Storms for Dams in Tennessee .....	8-22
Table 8-3	Broad-Crested Weir Coefficient C Values as a Function of Weir Crest Breadth and Head .....	8-23
Table 8-4	Example Tabulation of Storage Characteristics Curves .....	8-24
Table 8-5	Storage Indication Method—Example 8-1 Calculations .....	8-25
Table 8-6	Example 8-2 Runoff Hydrographs.....	8-26
Table 8-7	Example 8-2 Stage-Discharge-Storage Data .....	8-27
Table 8-8	Example 8-2 Reservoir Routing for the 2-Year Storm .....	8-28
Table 8-9	Example 8-2 Reservoir Routing for the 10-Year Storm .....	8-29
Table 8-10	Mean Monthly Evaporation Data.....	8-30
Table 9-1	Annual Rainfall Factor (R) Values for 2-, 5-, and 20-Year Return Periods for Nashville and Davidson County.....	9-13
Table 9-2	Expected Single Storm Rainfall Factor (R) Values for Nashville and Davidson County .....	9-13
Table 9-3	SCS Soil Erodibility Data .....	9-14
Table 9-4	Estimated Relative Soil Losses from Successive Equal-Length Segments of a Uniform Slope .....	9-19
Table 9-5	Surface Stabilization ( $C_s$ ) Factors for Bare Soil Conditions.....	9-20
Table 9-6	Surface Stabilization ( $C_s$ ) Factors for Permanent Pasture, Rangeland, Idle Land, and Grazed Woodland .....	9-21
Table 9-7	Surface Stabilization ( $C_s$ ) Factors for Undisturbed Woodland.....	9-22
Table 9-8	Mulch Surface Stabilization ( $C_s$ ) Factors and Length Limits for Construction Slopes .....	9-23



Table 9-9	Surface Stabilization ( $C_s$ ) Factors for Selected Methods of Surface Stabilization.....	9-24
Table 9-10	Surface Stabilization ( $C_s$ ) Factors for Mechanically Disturbed Woodland Sites.....	9-25
Table 9-11	Guidelines for Selecting Vegetative Cover.....	9-27
Table 9-12	Example Calculation of the Surface Stabilization ( $C_s$ ) Factor for Exposure Scheduling .....	9-28
Table 10-1	Suggested Outlet Protection Type Based on Froude Number and Velocity .....	10-26
Table 10-2	Experimental Coefficients for Culvert Outlet Scour .....	10-27
Table 10-3	Culvert, Channel, Scour, and Other Site Data Computation Form.....	10-28
Table 10-4	Riprap Outlet Basin Computation Form.....	10-29
Table 10-5	USBR Type II Basin Computation Form.....	10-30





## List of Figures

Figure 2-1	Intensity-Duration-Frequency Curves and Depth-Duration Data for Metro Nashville and Davidson County, Tennessee .....	2-61
Figure 2-2	Areal Reduction Factors for Precipitation Durations from 5 Minutes to 24 Hours.....	2-62
Figure 2-3	24-Hour Rainfall Hyetograph for Metro Nashville Area.....	2-63
Figure 2-4	Kinematic Wave Nomograph for Estimating Overland Flow Travel Time .....	2-64
Figure 2-5	Average Velocities for Estimating Travel Time for Shallow Channel Flow .....	2-65
Figure 2-6	100-Year Return Period Peak Runoff Rate Regression Equations .....	2-66
Figure 2-7	Unit Peak Discharge, $q_u$ , for SCS Type II Rainfall Distribution .....	2-67
Figure 2-8	SCS Dimensionless Unit Hydrograph and Mass Curve .....	2-68
Figure 3-1	Manning's n Values for Vegetated Channels .....	3-43
Figure 3-2	Open Channel Geometric Relationships for Various Cross Sections.....	3-44
Figure 3-3	Trapezoidal Channel Geometry .....	3-45
Figure 3-4	Nomograph for the Solution of Manning's Equation .....	3-46
Figure 3-5	Solution of Manning's Equation for Trapezoidal Channels .....	3-47
Figure 3-6	Trapezoidal Channel Capacity Chart.....	3-48
Figure 3-7	Protection Length, $L_p$ , Downstream of Channel Bend .....	3-49
Figure 3-8	Riprap Lining Bend Correction Coefficient .....	3-50
Figure 3-9	Riprap Lining Specific Weight Correction Coefficient.....	3-51



Figure 3-10	Riprap Lining $d_{30}$ Stone Size as a Function of Mean Velocity and Depth .....	3-52
Figure 3-11	Riprap Lining Thickness Adjustment for $d_{85}/d_{15} = 2.0$ to 2.3.....	3-53
Figure 3-12	Nomograph for Solving the Rectangular Channel Hydraulic Jump Equation .....	3-54
Figure 4-1	Nomograph for Flow in Triangular Gutter Sections.....	4-15
Figure 4-2	Ratio of Frontal Flow to Total Gutter Flow.....	4-16
Figure 4-3	Pavement Section Flow and Intercept for 30-foot Pavement with Curb (No Gutter) and 8-foot Spread.....	4-17
Figure 4-4	Pavement Section Flow and Intercept for 30-foot Pavement with 24-inch Curb and Gutter (18-inch Gutter) and 8-foot Spread.....	4-18
Figure 4-5	Pavement Section Flow and Intercept for 38-foot Pavement with 24-inch Curb and Gutter (18-inch Gutter) and 8-foot Spread.....	4-19
Figure 4-6	Grate Inlet Frontal Flow Interception Efficiency.....	4-20
Figure 4-7	Grate Inlet Side Flow Interception Efficiency .....	4-21
Figure 4-8	Hydraulic Capacity of Nashville Standard Grate Inlets Under Sump Conditions.....	4-22
Figure 4-9	Grate Inlet Capacity in Sump Conditions .....	4-23
Figure 5-1	Culvert Design Flow Chart .....	5-28
Figure 5-2	Culvert Design Form.....	5-29
Figure 5-3	Tapered Inlet Design Form .....	5-30
Figure 5-4	Mitered Inlet Design Form.....	5-31
Figure 5-5	Inlet Control Chart for Circular Concrete Pipe Culverts .....	5-32
Figure 5-6	Outlet Control Chart for Circular Concrete Pipe Culverts	



	Flowing Full .....	5-33
Figure 5-7	Inlet Control Chart for Circular CMP Culverts .....	5-34
Figure 5-8	Outlet Control Chart for Circular CMP Culverts Flowing Full .....	5-35
Figure 5-9	Outlet Control Chart for Structural Plate CMP Culverts Flowing Full .....	5-36
Figure 5-10	Inlet Control Chart for Concrete Box Culverts .....	5-37
Figure 5-11	Outlet Control Chart for Concrete Box Culverts Flowing Full .....	5-38
Figure 5-12	Inlet Control Chart for oval Concrete Pipe Culverts—Long Axis Horizontal .....	5-39
Figure 5-13	Inlet Control Chart for Oval Concrete Pipe Culverts—Long Axis Vertical .....	5-40
Figure 5-14	Outlet Control Chart for Oval Concrete Pipe Culverts Flowing Full—Long Axis Horizontal or Vertical .....	5-41
Figure 5-15	Inlet Control Chart for CMP Arch Culverts .....	5-42
Figure 5-16	Outlet Control Chart for CMP Arch Culverts Flowing Full .....	5-43
Figure 5-17	Outlet Control Chart for Structural Plate CMP Arch Culverts (18-inch Corner Radius) Flowing Full .....	5-44
Figure 5-18	Inlet Control Chart for Circular Pipe Culverts with Beveled Ring .....	5-45
Figure 5-19	Critical Depth Chart for Rectangular Sections .....	5-46
Figure 5-20	Critical Depth Chart for Circular Pipe .....	5-47
Figure 5-21	Critical Depth Chart for Oval Concrete Pipe—Long Axis Vertical .....	5-48
Figure 5-22	Critical Depth Chart for Oval Concrete Pipe—Long Axis Horizontal .....	5-49
Figure 5-23	Critical Depth Chart for Standard CMP Arch .....	5-50
Figure 5-24	Critical Depth Chart for Structural Plate CMP Arch .....	5-51



Figure 5-25	Throat Control Chart for Side-Tapered Inlets to Pipe Culvert (Circular Section Only).....	5-52
Figure 5-26	Face Control Chart for Side-Tapered Inlets to Pipe Culvert (Non-Rectangular Sections Only).....	5-53
Figure 5-27	Throat Control Chart for Box Culverts with Tapered Inlets.....	5-54
Figure 5-28	Face Control Chart for Box Culverts with Side-Tapered Inlets .....	5-55
Figure 5-29	Face Control Chart for Box Culverts with Slope-Tapered Inlets .....	5-56
Figure 5-30	Typical Side-Tapered Inlet Details .....	5-57
Figure 5-31	Side-Tapered Inlet with Upstream Depression Contained between Wingwalls.....	5-58
Figure 5-32	Side-Tapered Inlet with Upstream Sump.....	5-59
Figure 5-33	Slope-Tapered Inlet with Vertical Face .....	5-60
Figure 5-34	Slope-Tapered Inlet with Mitered Face .....	5-61
Figure 5-35	Inlet Edge Conditions, Face Section, Rectangular Tapered Inlets.....	5-62
Figure 5-36	Discharge Coefficients for Roadway Overtopping.....	5-63
Figure 5-37	Culvert Design Form Data for Example 5-1 .....	5-64
Figure 5-38	Culvert Design Form Data for Example 5-2.....	5-65
Figure 5-39	Culvert Design Form Data for Example 5-3 .....	5-66
Figure 5-40	Roadway Overtopping Data for Example 5-3 .....	5-67
Figure 5-41	Culvert Design Form Data for Example 5-4.....	5-68
Figure 5-42	Tapered Inlet Design Form Data for Example 5-4 .....	5-69
Figure 5-43	Results for Example 5-4.....	5-70



Figure 6-1	Hypothetical Storm Sewer System Layout for Demonstrating Hydrologic Calculations .....	6-21
Figure 6-2	Triangular Approximation of Inlet Hydrographs.....	6-22
Figure 6-3	Inlet Hydrograph Results for Segment $M_1 - M_2$ of the Hypothetical System in Figure 6-1 .....	6-23
Figure 6-4	Inlet Hydrograph Results for Segment $M_2 - M_3$ of the Hypothetical System in Figure 6-1 .....	6-24
Figure 6-5	Inlet Hydrograph Results for Segment $M_3 - M_4$ of the Hypothetical System in Figure 6-1 .....	6-25
Figure 6-6	Inlet Hydrograph Results for Segment $M_4 - O$ of the Hypothetical System in Figure 6-1 .....	6-26
Figure 6-7	Determination of Pressure vs. Open Channel Flow Conditions In Storm Sewer Systems .....	6-27
Figure 6-8	Storm Sewer Bend Loss Coefficient.....	6-28
Figure 6-9	Efficient Manhole Shaping.....	6-29
Figure 6-10	Inefficient Manhole Shaping.....	6-30
Figure 6-11	Circular Pipe Nomograph for Solving Manning's Equation .....	6-31
Figure 6-12	Circular Pipe Partial Flow Capacity Chart.....	6-32
Figure 6-13	Circular Pipe Partial Flow Velocity Chart.....	6-33
Figure 7-1	Plan and Cross Section of Spur Dike.....	7-7
Figure 8-1	Example Multi-Stage Control Structure .....	8-31
Figure 8-2	Sharp-Crested "V" Notch Weir Discharge Coefficients.....	8-32
Figure 8-3	Example Stage-Storage Curve .....	8-33



Figure 8-4	Example Stage-Discharge Curve .....	8-33
Figure 8-5	Illustrations of Weir Flow Control Structures .....	8-34
Figure 8-6	Dimensions Used for Design of a Proportional Weir .....	8-35
Figure 8-7	Triangular Shaped Hydrographs for Preliminary Estimate of Required Storage Volume.....	8-36
Figure 8-8	Example Storage Characteristics Curves .....	8-37
Figure 8-9	Example 8-2 Storage Characteristics Curves.....	8-38
Figure 8-10	Example 8-2 Pre- and Post-Development Runoff Hydrographs and Routed Outflow Hydrograph for the 2-Year Design Storm.....	8-39
Figure 8-11	Example 8-2 Pre- and Post-Development Runoff Hydrographs and Routed Outflow Hydrograph for the 10-Year Design Storm.....	8-40
Figure 8-12	Mass Routing Example for Land-Locked Retention Areas .....	8-41
Figure 8-13	Cumulative Rainfall Data for the 100-Year, 10-Day Design Storm.....	8-42
Figure 9-1	Erosion Index (EI) Distribution Curve Applicable to Nashville and Davidson County .....	9-29
Figure 9-2	Length-Slope Factor Chart for the USLE .....	9-30
Figure 9-3	Conceptual Sketch of Typical Concave and Convex Slopes .....	9-31
Figure 10-1	Design of Riprap Apron under Minimum Tailwater Conditions.....	10-31
Figure 10-2	Design of Riprap Apron under Maximum Tailwater Conditions .....	10-32
Figure 10-3	Riprap Apron Schematic for Uncertain Tailwater Conditions .....	10-33
Figure 10-4	Details of Riprap Outlet Basin.....	10-34
Figure 10-5	Dimensionless Rating Curves for the Outlets of Rectangular Culverts on Horizontal and Mild Slopes .....	10-35



Figure 10-6	Dimensionless Rating Curves for the Outlets of Circular Culverts on Horizontal and Mild Slopes .....	10-36
Figure 10-7	Relative Depth of Scourhole vs. Froude Number at Brink of Culvert with Relative Size of Riprap as a Third Variable .....	10-37
Figure 10-8	Distribution of Centerline Velocity for Flow from Submerged Outlets ...	10-38
Figure 10-9	Riprap Size for Protection Downstream of Outlet Basins .....	10-39
Figure 10-10	Schematic of Baffled Outlet.....	10-40
Figure 10-11	W/d vs. Froude Number for Baffled Outlet Basins .....	10-41
Figure 10-12	USBR Type II Outlet Basin .....	10-42
Figure 10-13	Definition Sketch of Supercritical Flow Expansions.....	10-43
Figure 10-14	Length of Jump on Horizontal Floor for USBR Type II Outlet Basin .....	10-44
Figure 10-15	Fr vs. $y_o/r$ for Flow Transitions.....	10-45
Figure 10-16	Tailwater Depth for USBR Type II Outlet Basin .....	10-46
Figure 13-1	SPPP Phases .....	13-3