

**Storm Water Division
Operating Policies
Routine Maintenance (RoM)**



Policy No.: RoM-6	Page <u> 1 </u> of <u> 1 </u>
Subject: Driveway Pipe Maintenance	Effective Date: 10-1-02
Applies To: All Stormwater Projects	<input type="checkbox"/> New Issue <input checked="" type="checkbox"/> Partial Revision <input type="checkbox"/> Complete Revision
Purpose:	To establish guidelines for the cleaning, repair, and replacement of driveway pipes.
Policy:	<p>Culverts under driveways (driveway pipes) will be cleared of any obstruction deemed to hinder the ability of the culvert to function as designed with the following exceptions:</p> <ol style="list-style-type: none"> 1. Culverts that are so obstructed that it is more cost effective to replace the culvert instead of clearing the obstruction(s) may be replaced. 2. Culverts that do not meet the current design criteria for minimum pipe size, recommended pipe material, or conveyance capacity may be replaced. <p>The portion of the driveway that must be removed for the installation of the pipe will be restored in kind (ie: asphalt will be replaced with asphalt, concrete will be replaced with similar concrete).</p>
Revision No.: 1	Issued By: <i>[Signature]</i>
Revision Date: 10-15-07	

RECEIVED
DEC 4 2014
METROPOLITAN
CLERK