



GENERAL NOTES

1. FOR CURB RADIUS EQUAL TO OR LESS THAN 25'.
2. SEE CURB RAMP STANDARD DRAWINGS FOR CONSTRUCTION DETAILS.
3. ALL MARKINGS TO CONFORM TO MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
4. THE LAYOUT, SIZE, DIMENSIONS, HEIGHT OF THE DETECTABLE WARNINGS SHALL MEET THE LATEST DESIGN STANDARDS AS ISSUED BY THE ACCESS BOARD.
5. THE DETECTABLE WARNINGS AND INSTALLATIONS SHALL MEET THE MPW SPECIFICATION 02523.
6. IN THE EVENT OF ANY CONFLICT, DISCREPANCY, OR INCONSISTENCY AMONG THE PLANS AND THESE STANDARD DETAILS, THE REQUIREMENTS OF THE STANDARD DETAILS SHALL GOVERN.
7. THE COLOR OF THE DETECTABLE WARNING STRIP SHALL BE "SAFETY YELLOW".

NOT TO SCALE

METROPOLITAN GOVERNMENT OF
NASHVILLE AND DAVIDSON COUNTY
DEPARTMENT OF PUBLIC WORKS

DETECTABLE WARNINGS
AT CURB RETURNS WITH
RADIUS 25' OR LESS

DWG. NO. ST-329

DIR. OF ENG.:

Mark My DATE: 6/17/05

REVISED: 06/17/05
REVISED: 08/13/04
REVISED: